REA35OUT KC



Air conditioner – outdoor unit (SINGLE)





Heating at -20°C

Full DC Inverter

Auto Defrosting

Easy Maintenance

1 W Standby

Unite type: External unit

Operating temperature range in heating mode (°C): -20- 24 Operating temperature range in cooling mode (°C): -15 - 50

Temperature setting range (°C): 16-30

Operating mode: Inverter

Refrigerant: R32

EER: 2.98

Energy efficiency class - heating Average: A+ Energy efficiency class - heating Warmer: A+++

Speed level of outdoor ventilator: 3 Air conditioner marketing category: Split Maximum connectable indoor units: 1 Speed level of indoor ventilator: 7

Heating design load (Pdesignh)-average heating season: 2.7 kW Declared capacity (Pdh(Tj))-average heating season: 2.7 kW

Operating range - heating: 20 g/m

Version: mono

Cooling capacity: 3.4 kW

Silent operation for more comfort: Yes, 19dB(A)

Minimum audio power: 62 dB(A)re 1 pW

Heating power: 3,800 W

Consumption in standby mode: 1 W

Cooling hourly energy consumption: 1.1 kWh Heating hourly energy consumption: 1.1 kWh

Frequency: 50 Hz Cooling power: 3,400 W Refrigerant charge: 0.58 kg

Minimum sound pressure: 48 dB(A)2x10-5Pa Maximum sound pressure: 54 dB(A)2x10-5Pa Connecting power at heating: 1,050 W Connecting power at cooling: 1,140 W

Air flow - min: 1,000 m³ Air flow - max: 1.500 m³ Diameter of liquid pipe: 6.35 mm Diameter of gas pipe: 9.53 mm Maximum pipe length: 20 m Maximum height difference: 10 m Nominal current - cooling: 5 amp Nominal current - heating: 4.7 amp

Ratio SEER - cooling: 6,1 SCOP - Average season: 4 SCOP - Warmer season: 5.1

COP: 3.62

Minimum sound pressure: 48 dB(A)2x10-5Pa Maximum sound pressure: 54 dB(A)2x10-5Pa Dimensions (W×H×D): 66 x 48.3 x 24 cm

Dimensions of packed product (W×H×D): 78 x 53 x 31.5 cm

Net weight: 22 kg Gross weight: 25 kg

Consumption in standby mode: 1 W



Nominal current of fuse: 15 amp

Product code: **20003668** EAN code: **3838782495649**