



#### Flexible Expansion

Up to 12 units in parallel, 15KWh--921KWh capacity



## Ultra Safe

Intelligent fire extinguishing system, react within 5 seconds



#### 1C Rate

Suitable for grid frequency regulation, charging stations and other scenarios, cost saving



## Easy Installation

O wiring, rackless free stacking, plug-and-play, one cluster installation in 30min



# Long-term Reliability

LFP cells, 6000+ cycles, 0 decay in 3 years, 10 years long warranty



## Module Mixing

Free mixing of modules within three years

# **Specification**

Model	STACK100
Battery Type	LiFePO4
Module Voltage/Capacity	51.2V/100Ah
Single Module Weight	47Kg
System Modules Serial Number	3~15
System Energy Range	15.36-76.8kWh
Operating Voltage	134-864V
Recommended Charge/Discharge Current	50A (0.5C)
Max.Charge/Discharge Current	100A (1C)
Peak Discharge Current(2min 25°C)	125A(1.25C)
Depth of Discharge	95%
Communication	CAN/RS485
Cycle Life *	Unlimited cycles / 10 Years
Max. Single Cluster Dimension[W*D*H](mm)	591 / 390 / 1700-11 module
Charging Temp. Range	0~55°C
Discharging Temp. Range	-20~55°C
Protection Level	IP2O
Fire Protection System	Aerosol fire extinguisher
Installation method	Stack type
Cooling method	Forced wind cooling
WiFi Module	Built-in WiFi module; APP OTA function
Certification & Safety Standard	CE-EMC/CE-RED/62619/63056/62477/62040/UN38.3
Compatible Inverters	Ingeteam/Solis/GoodWe/Growatt/Solplanet/SAJ/DEYE/Hoymiles/SOLINTEG ect.

<sup>\*</sup> Test conditions: 0.2C Charging & Discharging. @25°C, 95% DOD

